



The PXI-52100 platform features the industry-standard, 8-slot/14-slot/18-slot PXI/ CompactPCI backplane integrated into a 3U Eurorack enclosure with a bay for removable power supplies.

With hot pluggable power supplies and optional battery packs, 52100 offers the widest application range of all chassis on the market.

Mounting attachment locations allow the PXI-52100 to be mounted against a wall or bulkhead, with the card cage extended in front for easy access to adapter card. The rear of the card cage is enclosed to protect the backplane from contamination as well as provide shielding for RFI/EMI.

Power Supplies

The PXI-52100 chassis accepts removable power supply modules of the cPWR series. The power connector is a PCI 47M 400A1 connector, compliant with PICMG 2.11 Power Interface Specification standard, a mechanically and electrically roBust connector.

8-Slot/ 14-Slot/ 18-Slot

KEY FEATURES

- High-capacity 8-slot/14-slot/18-slot PXI/cPCI backplane
- Low-profile 4U rugged design
- Easily convertible for rack or bench used
- 51 CFM for 3/4/6 high pressure tube-axial fans
- 175W/ea plug-in power supply
- Removable fans and air filter
- Optional DC (24V) input configuration available
- Comprehensive EMC shielding

ORDERING INFORMATION

	Chassis (w/Backplane)	AC Power Supply (Input 110/220Vac)	DC Power Supply (Input 24Vdc)
52101-1 / 52102-1	1	2	
52101-2 / 52102-2	1		2
52105-1	1	4	

SPECIFICATIONS

Model	52101	52102	52105
Backplane	• 3U-sized; PXI backplane • Compliant with PXI Specification R2.0 • PXI and CompactPCI (PICMG 2.0 R3.0) 3U modules		
Accessible Slots	8 slots	14 slots	18 slots
Power Supply	Output: 175W max. x 2 sets • AC Input: 90V to 264V • DC Input: 18V to 36V		
BUS Width	64-bit		
Rack Mounting	4U, 19" EIA format		
Cooling Capacity	Slot cooling capacity in worst-case slot is 50W		
Module Cooling	Forced air circulation (positive pressurization) via 51 cfm (x3)	Forced air circulation (positive pressurization) via 51 cfm (x4)	Forced air circulation (positive pressurization) via 51 cfm (x6)
Slot Airflow Direction	P1 to P2, bottom of module to top of module		
Module Cooling Fan MTBF	75,000+hr		
Weight	8.5kg	9.5kg	13.5kg
Dimensions (WxDxH) mm	• Desktop: 442.2 x 257.8 x 192.1 • Rack-mount: 482.6 x 257.8 x 177.0		• Desktop: 442.2 x 481.2 x 192.1 • Rack-mount: 482.6 x 481.2 x 177.0
Operating Temp.	0°C ~ 55°C		
Storage Temp.	-20°C ~ 70°C		
Humidity	10 ~ 95% @ 40°C, non-condensing		
Packaged Vibration	5 ~ 100Hz: 0.015G2/Hz; 100 ~ 200Hz: -6 dB/Oct; 200 Hz: 0.0038 G2/Hz		
Unpackaged Vibration	5 ~ 55 ~ 5Hz 0.38mm Peak to Peak		
Drop Test	Falling Height: 76 cm; Falling: 1 corner/3 edges/6 faces		
Shock Test (Operating)	Acceleration: 10G; Pulse width: 11ms; Pulse shape: half sine wave; No. of shock: 3 shocks for bottom side		